

## AN OVERVIEW OF WSN AND ITS APPLICATIONS

<sup>1</sup>Bhawna Sharma, <sup>2</sup>Er. Kapil, <sup>3</sup>Er.Aakash Goyal

<sup>1</sup>M. tech. Student, SPITM, Sonapat; cse.bhavnakaushik@gmail.com

<sup>2</sup>H.O.D., CSE deptt., SPITM, Sonapat; life.kapil@gmail.com

<sup>3</sup>A.P. CSE deptt., JIET, Jind; aakash.goyal99@gmail.com

**Abstract:** WSN is a network that consist of microelectronics system nodes having limited power and processing capability which record and report various physical variables related to the environment in which they are deployed. In this paper we will present various features of wireless sensor network and its various application in number of domains. We will also point some issues of wireless networks in the paper.

**Keywords:** sensor nodes, topology, antenna, deployment.

### I. WIRELESS SENSOR NETWORK

Wireless Sensor Network (WSN) consists of spatially distributed autonomous sensors to monitor physical or environmental conditions, such as temperature, sound, vibration, pressure, motion or pollutants and to cooperatively pass their data through the network to a main location. The more modern networks are bi-directional, enabling also to control the activity of the sensors. The development of wireless sensor networks was motivated by military applications such as battlefield surveillance; today such networks are used in many industrial and consumer application, such as industrial process monitoring and control, machine health monitoring, environment and habitat monitoring, healthcare applications, home automation, and traffic control.

The WSN is built of "nodes" from a few to several hundreds or even thousands, where each node is connected to one (or sometimes several) sensors. Each such sensor network node has typically several parts: a radio transceiver with an internal antenna or connection to an external antenna, a microcontroller, an electronic circuit for interfacing with the sensors and an energy source, usually a battery or an embedded form of energy harvesting. A sensor node might vary in size from that of a shoebox down to the size of a grain of dust, although functioning "motes" of genuine microscopic dimensions have yet to be created. The cost of sensor nodes is similarly variable, ranging from hundreds of dollars to a few pennies, depending on the complexity of the individual sensor nodes. Size and cost constraints on sensor nodes result in corresponding constraints on resources such as energy, memory, computational speed and communications bandwidth. The topology of the WSNs can vary from a simple star network to an advanced multi-hop wireless mesh network. The propagation technique between the hops of the network can be routing or flooding.[1,2]



© IJRPS International Journal for Research Publication & Seminar

**Note :** For Complete paper/article please contact us [info@jrps.in](mailto:info@jrps.in)

Please don't forget to mention reference number , volume number, issue number, name of the authors and title of the paper

